EMAVERICK MAX X® mr

HIGHLIGHTS

- 101-hp Rotax® 1000R V-twin engine with high-flow dynamics
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok[‡] QE auto-locking front differential
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT) with Quick Response System (QRS)
- Mid-engine layout for mass centralization
- Double A-arm front suspension with 12 in. (30.5 cm) of travel
- Torsional Trailing A-arms (TTA) independent rear suspension with 12 in. (30.5 cm) of travel
- · Front sway bar

- Front and rear FOX[†] 2.5 PODIUM QS3[†]
- 14-in. cast-aluminum wheels with 30-in. Gorilla Axle Silverback[†] tires
- Strategically positioned engine air intake and CVT inlets / outlets
- 4,500-lb (2,041 kg) winch
- · Extra low L-Gear
- Analog / Digital gauge
- Passenger handhold and grab bar
- X-package seat trims, graphics and sponsor decals



Hyper Silver, Black & Octane Blue / 1000R

ENGINE	1000R
Туре	101 hp, Rotax 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow, L / H / N / R / P, Extra low L-Gear
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar 12-in. (30.5 cm) travel
Front Shocks	FOX 2.5 PODIUM QS3 Piggyback compression adjustment
Rear Suspension	Torsional Trailing A-arms (TTA) independent with sway bar 12-in. (30.5 cm) travel
Rear Shocks	FOX 2.5 PODIUM QS3 Piggyback compression adjustment

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers

TIRES / WHEELS	
Front Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	148 x 67.9 x 81.9 in. (376 x 172 x 208 cm)	
Wheelbase	113.8 in. (289.1 cm)	
Ground Clearance	14.5 in. (36.8 cm)	
Dry Weight*	1,571.8 lb (713 kg)	
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach	
Storage Capacity	Glove box: 4.5 gal (17.2 L) Center console: 0.3 gal (1.3 L)	
Towing Capacity	N/A	
Fuel Capacity	10 gal (37.8 L)	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	N/A
		Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240 W from four 60-W projectors with tail lights / brake lights
Winch	4,500-lb (2,041 kg) winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S. $^{\text{\tiny TM}}$)

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage



