## arenegade X° xc

## **HIGHLIGHTS**

- Rotax® V-twin engine options
- Front and rear FOX<sup>†</sup> 1.5 PODIUM<sup>†</sup> RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshot† ATR tires
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry

- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok<sup>‡</sup> QE auto-locking front differential
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



White, Black & Can-Am Red / 850 / 1000R
Triple Black / 1000R

ENGINES	850	1000R	
Туре	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	FOX 1.5 PODIUM RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlock

DIMENSIONS / CAPACITIES		
LxWxH	86 x 46 x 49 in. (218.4 x 116.8 x 124 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	10.5 in. (26.7 cm)	
Seat Height	34.5 in. (87.7 cm)	
Engine / Dry Weight*	850 / 668 lb (303 kg) 1000R / 692 lb (314 kg)	
Rack Capacity	Rear: 35 lb (16 kg)	
Storage Capacity	N/A	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connecto in the back (15-A)
		Lighting	240 W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, aluminum skid plate		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



