amaverick x3 x ds turbo r

DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

POWERFUL

- Industry leading 172 hp turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

- · TTX suspension with industry leading travel
- Ultra efficient and
- lightweight chassis
- Sharpest handling features



Platinum Satin

SPECIFIC TO X ds PACKAGE

- 14-in. aluminum beadlock wheels with 29-in. Maxxis Bighorn[†] 2.0 tires
- Front and rear 20-in. (50.8 cm) suspension travel
- Fully adjustable FOX[†] 2.5 PODIUM RC2[†] Piggyback shocks
- Painted color

ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] X auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

TIRES / WHEEL	.S
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14-in. aluminum beadlock

SUSPENSIONS			
Front Suspension	Double A-arm with sway bar 50.8 cm travel		
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression and rebound adjustments		
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 50.8 cm travel		
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound adjustments and bottom-out control		
BRAKES			
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers		

DIMENSIONS /	CAPACITIES	
LxWxH	332.7 x 162.5 x 167.6 cm	
Wheelbase	259.1 cm	
Ground Clearance	35.6 cm	
Estimated Dry Weight	675.9 kg	
Cage / Chassis	Dual-phase 980 steel, fully welde	
Rack Capacity	91 kg with LinQ™ quick-attach	
Storage Capacity	Total: 9.4 L Glove box: 6.2 L Center console: 2.8 L Cup holders: 0.4 L	
Fuel Capacity	40 L	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	Integrated front bumper, full High Molecular Weight (HMW) skid plate and quarter-doors
		Instrumentation	Lighter type DC outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	2 years
Extended	Up to 30 months B.E.S.T. coverage



