

2016 MAVERICK™ X® ds TURBO

HIGHLIGHTS

- Rotax® 976 cc Turbocharged V-twin engine with forged pistons, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
- Tri-Mode Dynamic Power Steering (DPS™) ⁽¹⁾
- Visco-Lok‡ QE auto-locking front differential
- Intelligent Throttle Control (ITC™)
- Continuously Variable Transmission (CVT) with Quick Response System (QRS)
- Mid-engine layout for mass centralization
- Double A-arm front suspension with 15 in. (38.1 cm) of travel
- Torsional Trailing A-arms independent rear suspension (TTA) with 16 in. (40.6 cm) of travel ⁽²⁾
- Front and rear FOX 2.5 PODIUM RC2† shocks with dual speed compression, rebound and preload adjustments. The rear shocks feature bottom-out control and spring crossover
- 14-in. aluminum beadlock wheels with 28-in. Maxxis Bighorn 2.0† tires ⁽²⁾
- High-strength, 200-lb (91 kg) multipurpose rear rack with LinQ™ quick-attach system
- Analog / Digital gauge
- Adjustable driver's seat and tilt steering
- Passenger handhold and grab bar
- X-package seat trims and graphics



■ Carbon Black & Manta Green / 1000R TURBO

ENGINE

| | 1000R TURBO |
|----------------------|--|
| Type | Rotax 976 cc Turbocharged V-twin engine with forged pistons, liquid cooled with integrated intercooler & Donaldson high-performance air filter |
| Fuel Delivery System | Intelligent Throttle Control (ITC) with Electronic Fuel Injection (EFI) |
| Transmission | Quick Response System (QRS) CVT with high airflow, L / H / N / R / P |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) ⁽¹⁾ |

SUSPENSIONS

| | |
|------------------|--|
| Front Suspension | Double A-arm 15 in. (38.1 cm) travel |
| Front Shocks | FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound and dual rate spring preload adjustments |
| Rear Suspension | Torsional Trailing A-arms independent rear suspension (TTA) with sway bar 16 in. (40.6 cm) travel ⁽²⁾ |
| Rear Shocks | FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound, dual rate spring preload adjustments and spring crossover, bottom-out control |

BRAKES

| | |
|-------|--|
| Front | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers |

FEATURES

| | | | |
|-------|--|-------------------|--|
| Gauge | Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off | Protection | Front bumper |
| Winch | Prewired for winch | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| | | Lighting | 240-W from four 60-W projectors with tail lights / brake lights |
| | | Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) |

WARRANTY

EC models : 2-Year Warranty.

All EC models are limited to 15 Kw/20 hp and equipped with EC homologation required equipments including without restriction horn, mirrors and blinkers. EC models engines are compliant with EC standards in force. Towing capacities of EC models respect applicable EC homologation requirements.

©2015 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

TIRES / WHEELS

| | |
|-------------|---|
| Front Tires | Maxxis Bighorn 2.0 ⁽²⁾ 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm) |
| Rear Tires | Maxxis Bighorn 2.0 ⁽²⁾ 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm) |
| Wheels | 14 in. aluminum beadlock ⁽²⁾ |

DIMENSIONS / CAPACITIES

| | |
|------------------|--|
| L x W x H | 117.3 x 64 x 74.2 in. (297.9 x 162.5 x 188.5 cm) |
| Wheelbase | 88 in. (223.5 cm) |
| Ground Clearance | 13 in. (33 cm) |
| Dry Weight | 1,399 lb (634.6 kg) |
| Rack Capacity | 200 lb (91 kg) with LinQ quick-attach |
| Storage Capacity | Glove box: 4.5 gal (17.2 L) Center console: 0.3 gal (1.3 L) |
| Towing Capacity | N/A |
| Fuel Capacity | 10 gal (37.8 L) |

⁽¹⁾ With DPS kit

⁽²⁾ With Ready to Race kit

can-am



Can-AmOffroad.com