

SPECIFICATII TEHNICE

MOTOR

Tip	eSP+ SOHC - 4 timpi, 4 supape
Capacitate cilindrica	125 cc
Diametru x Cursa	53.5 x 55.5 mm
Raport compresie	11.5 : 1
Putere maxima	12,5 CP / 8.750 rot/min
Cuplu maxim	11.8 Nm / 6.500 rot/min

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Consum carburant	2,1 l/100 km
Capacitate rezervor carburant	8,1 l
Capacitate rezervor ulei	0,9 l

EMISII CO2 & NORMA DE POLUARE

Norma de poluare	Euro 5
Emisii CO2	46 g/km

SISTEM ELECTRIC

Sistem de aprindere	Gestionat electronic
Demaror	Electric
Lumini	LED

TRANSMISIE

Tip	CVT
Ambreiaj	Automatic; centrifugal
Transmisie finala	V-Matic

DOTARI

Smart Key	
Display Digital – LCD	
Priza USB-C	
Lumini Full LED	
Honda Selectable Torque Control (HSTC)	



SUSPENSIE & ROTI

Tip	Fata	Furca telescopica (31 mm), cursa 89 mm
	Spate	Brat articulata din aluminiu cu suspensie dubla, cursa 95 mm
Jante	Fata	14M/C x MT2.75
	Spate	13M/C x MT3.50
Anvelope	Fata	110/70-14M/C
	Spate	130/70-13M/C

SISTEM DE FRÂNARE

Fata	Disc hidraulic de 220 mm, etrier cu 2 pistoane, ABS
Spate	Tambur de 130 mm

CADRU

Tip	Duplex Tubular - Otel
Dimensiuni (L x l x î)	1.935 x 740 x 1.105 mm
Ampatament	1.315 mm
Unghi inclinare furcă	26,3°
Cursa	80 mm
Inaltime sa	764 mm
Garda la sol	135 mm
Masa proprie	130 kg