2025 CAN-AM ORIGIN®



CAN-AM ORIGIN

- Adventure electric motorcycle
- Versatile motorcycle designed for On and Off-Road riding
- Available in 11kW and 35kW
- Lightweight design for excellent handling

PACKAGE HIGHLIGHTS

- 10.25 in. touchscreen display with BRP Connect® and Apple CarPlay®
 Liquid-cooled system: battery, inverter, motor and on-board charger
 Charging from 20-80 % in only 50 minutes
 Single-sided swingarm with chaincase
 Active and Passive Regen
 Reverse function

- LinQ* integration for accessorization
 Full KYB† suspension with 255 mm of suspension travel

*BRIGHT WHITE MODEL SHOWN

RAIN SPORT OFF-ROAD LINQ BRP CONNECT MODE MODE COMPATIBLE APPLE CARPLAY

Type	MOTOR	
Torque Motor Peak: 72 Nm from 0 to 4600 RPM Top Speed/Sustained 80 mph (129 km/h) Acceleration 4.3 seconds: 0-60 mph (0-100 km/h) BATTERY Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Front Tire Dunlop¹ D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Туре	ROTAX* E-POWER, liquid-cooled
Top Speed/Sustained 80 mph (129 km/h) Acceleration 4.3 seconds: 0-60 mph (0-100 km/h) BATTERY Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Power	
Acceleration 4.3 seconds: 0-60 mph (0-100 km/h) BATTERY Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Torque Motor	Peak: 72 Nm from 0 to 4600 RPM
BATTERY Type Integrated, lithium-ion Capacity 8,9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop b605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Top Speed/Sustained	80 mph (129 km/h)
Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min, (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop b605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Acceleration	4.3 seconds: 0-60 mph (0-100 km/h)
Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min, (20–80%) Level 2 (240 V) 1 hour 30 min, (0–100%) Charging Time: 3 hours 10 min, (0–100%) Charging Time: 1 hours 30 min, (0–100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop¹ 6065 90/90 R21 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	BATTERY	
Cooling System Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop	Туре	Integrated, lithium-ion
Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel Rear Suspension/ Travel Rear Suspension/ Travel Lyuan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan ¹-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Capacity	8,9 kWh
(when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan 1-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Cooling System	Liquid-cooled: battery, inverter and on-board charger
Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ -piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)		Combined (WMTC*): 71 miles (115 km)
Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Function	
Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan † 2-piston floating caliper, 320 mm disc Rear Brake J.Juan † 2-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Charger	On-board charger: 6.6 kW (Level 1 & Level 2 compatible)
Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel KYB 43 mm inverted fork / 255 mm (10 in.) Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan† 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop† D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Connector	Type 1 J1772
Level 1 (120 V) 5 hours 15 min. (0-100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel KYB 43 mm inverted fork / 255 mm (10 in.) Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop¹ 6065 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)		
Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel Rear Suspension/ Travel rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)		
Final Drive Chaincase with silent chain Function Reverse function CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel Rear Suspension/ KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	DRIVETRAIN	
Function Reverse function CHASSIS Swingarm Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel KYB 43 mm inverted fork / 255 mm (10 in.) Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Transmission	Clutchless direct drive
CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Final Drive	Chaincase with silent chain
Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel KYB 43 mm inverted fork / 255 mm (10 in.) Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Function	Reverse function
Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel KYB 43 mm inverted fork / 255 mm (10 in.) Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	CHASSIS	
Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel Rear Suspension/ Travel rebound / 255 mm (10 in.) Front Brake J.Juan† 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop† D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Swingarm	Single-sided swingarm
Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Rake	30°
Travel Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Trail	118 mm (14.6 in.)
Travel rebound / 255 mm (10 in.) Front Brake J.Juan† 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop† D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)		KYB 43 mm inverted fork / 255 mm (10 in.)
Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop† D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)		
Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Front Brake	J.Juan [†] 2-piston floating caliper, 320 mm disc
Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Rear Brake	J.Juan 1-piston floating caliper, 240 mm disc
Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Front Tire	Dunlop [†] D605 90/90 R21 (with tube)
Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Rear Tire	Dunlop D605 120/80 R18 (with tube)
	Wheels	Spoked wheel, Carbon black
Rear Wheel Size 457 x 63.5 mm (18 x 2.5 in.)	Front Wheel Size	533 x 47 mm (21 x 1.85 in.)
	Rear Wheel Size	457 x 63.5 mm (18 x 2.5 in.)

COLOR

Bright White	
Carbon Black	
DIMENSIONS	
LxWxH	2,204 x 861 x 1,414 mm(86.8 x 33.9 x 55.7 in.)
(with mirrors)	
Wheelbase	1,503 mm (59 in.)
Seat Height	865 mm (34 in.)
Ground Clearance	274 mm (10.8 in.)
Curb Weight	187 kg (412 lb)
Maximum Vehicle Load	338 kg (745 lb)
INSTRUMENTATION	
Туре	10.25 in. touchscreen display with BRP Connect
Navigation System	Apple CarPlay
Drive Modes	Normal, ECO, Rain, Sport, Off-Road, Off-Road+
Handlebar Control	Backlit handlebar control module
SAFETY & SECURITY	
ABS	Anti-Lock Braking System
MTC	Motorcycle Traction Control
WARRANTY & EXTEN	DED SERVICE
Vehicle Warranty	2 years
Battery Warranty	5 years / 31,068 miles (50,000 km)
Extended Service Terms	
FEATURES	
	LED headlight Glove box with USB port LinQ anchor points Skid plate