# 2025 CAN-AM ORIGIN® '73



## CAN-AM ORIGIN '73

- Adventure electric motorcycle
- Versatile motorcycle designed for On and Off-Road riding
- Available in 11kW and 35kW
- Lightweight design for excellent handling

#### **PACKAGE HIGHLIGHTS**

- 10.25 in. touchscreen display with BRP Connect\* and Apple CarPlay\*
   Liquid-cooled system: battery, inverter, motor and on-board charger
   Charging from 20-80 % in only 50 minutes
   Single-sided swingarm with chaincase
   Active and Passive Regen
   Reverse function

- LinQ\* integration for accessorization
  Full KYB† suspension with 255 mm of suspension travel
- Premium package with exclusive coloration and trims
  \*Bright white model shown



Type	MOTOR	
Torque Motor Peak: 72 Nm from 0 to 4600 RPM Top Speed/Sustained 80 mph (129 km/h) Acceleration 4.3 seconds: 0-60 mph (0-100 km/h)  BATTERY Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW ( Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0-100%)  DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Front Brake JJuan¹ 2-piston floating caliper, 320 mm disc Front Tire Dunlop¹ D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm ( 21 x 1.85 in.)	Туре	ROTAX* E-POWER, liquid-cooled
Top Speed/Sustained 80 mph (129 km/h) Acceleration 4.3 seconds: 0-60 mph (0-100 km/h)  BATTERY Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%)  DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Power	
Acceleration 4.3 seconds: 0-60 mph (0-100 km/h)  BATTERY  Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%)  DRIVETRAIN  Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Torque Motor	Peak: 72 Nm from 0 to 4600 RPM
BATTERY Type Integrated, lithium-ion Capacity 8,9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km) Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%) Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%)  DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop b605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Top Speed/Sustained	80 mph (129 km/h)
Type Integrated, lithium-ion Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min, (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%)  DRIVETRAIN  Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop b605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Acceleration	4.3 seconds: 0-60 mph (0-100 km/h)
Capacity 8.9 kWh Cooling System Liquid-cooled: battery, inverter and on-board charger Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min, (20–80%) Level 2 (240 V) 1 hour 30 min, (0–100%) Charging Time: 3 hours 10 min, (0–100%) Charging Time: 1 hours 30 min, (0–100%) DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	BATTERY	
Cooling System  Estimated Range (when fully charged)  City: 90 miles (145 km) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function  Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772  Charging Time: 50 min. (20-80%) Level 2 (240 V) 1 hour 30 min. (0-100%)  Charging Time: 3 hours 10 min. (20-80%) Level 1 (120 V) 5 hours 15 min. (0-100%)  DRIVETRAIN  Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ Travel Rear Suspension/ Travel Rear Suspension/ Travel Rear Brake J.Juan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan¹ 2-piston floating caliper, 240 mm disc Front Tire Dunlop	Туре	Integrated, lithium-ion
Estimated Range (when fully charged) Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible) Connector Type 1 J1772 Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%) Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%)  DRIVETRAIN Transmission Clutchless direct drive Final Drive Chaincase with silent chain Function Reverse function  CHASSIS Swingarm Single-sided swingarm Rake 30° Trail 118 mm (14.6 in.) Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.) Travel Rear Suspension/ Travel Rear Suspension/ Travel Lyuan¹ 2-piston floating caliper, 320 mm disc Rear Brake J.Juan 1-piston floating caliper, 240 mm disc Front Tire Dunlop¹ D605 90/90 R21 (with tube) Rear Tire Dunlop D605 120/80 R18 (with tube) Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Capacity	8,9 kWh
(when fully charged)  Combined (WMTC*): 71 miles (115 km) Sustained 50 mph (80 km/h): 52 miles (84 km)  Function Active Regen, Passive Regen  Charger On-board charger: 6.6 kW (Level 1 & Level 2 compatible)  Connector Type 1 J1772  Charging Time: 50 min. (20–80%) Level 2 (240 V) 1 hour 30 min. (0–100%)  Charging Time: 3 hours 10 min. (20–80%) Level 1 (120 V) 5 hours 15 min. (0–100%)  DRIVETRAIN  Transmission Clutchless direct drive  Final Drive Chaincase with silent chain  Function Reverse function  CHASSIS  Swingarm Single-sided swingarm  Rake 30°  Trail 118 mm (14.6 in.)  Front Suspension/ Travel  Rear Suspension/ Travel KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)  Front Brake J.Juan 1-piston floating caliper, 320 mm disc  Rear Brake J.Juan 1-piston floating caliper, 240 mm disc  Front Tire Dunlop D605 120/80 R18 (with tube)  Wheels Spoked wheel, Carbon black  Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Cooling System	Liquid-cooled: battery, inverter and on-board charger
Charger         On-board charger: 6.6 kW ( Level 1 & Level 2 compatible)           Connector         Type 1 J1772           Charging Time:         50 min. (20-80%)           Level 2 (240 V)         1 hour 30 min. (0-100%)           Charging Time:         3 hours 10 min. (20-80%)           Level 1 (120 V)         5 hours 15 min. (0-100%)           DRIVETRAIN         Transmission           Clutchless direct drive           Final Drive         Chaincase with silent chain           Function         Reverse function           CHASSIS           Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/         KYB 43 mm inverted fork / 255 mm (10 in.)           Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan¹ -piston floating caliper, 240 mm disc           Front Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)		Combined (WMTC*): 71 miles (115 km)
Connector         Type 1 J1772           Charging Time:         50 min. (20-80%)           Level 2 (240 V)         1 hour 30 min. (0-100%)           Charging Time:         3 hours 10 min. (20-80%)           Level 1 (120 V)         5 hours 15 min. (0-100%)           DRIVETRAIN           Transmission         Clutchless direct drive           Final Drive         Chaincase with silent chain           Function         Reverse function           CHASSIS           Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/         KYB 43 mm inverted fork / 255 mm (10 in.)           Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan¹ 2-piston floating caliper, 240 mm disc           Front Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	Function	
Charging Time:         50 min. (20–80%)           Level 2 (240 V)         1 hour 30 min. (0–100%)           Charging Time:         3 hours 10 min. (20–80%)           Level 1 (120 V)         5 hours 15 min. (0–100%)           DRIVETRAIN           Transmission         Clutchless direct drive           Final Drive         Chaincase with silent chain           Function         Reverse function           CHASSIS           Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/         KYB 43 mm inverted fork / 255 mm (10 in.)           Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan † 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan † 2-piston floating caliper, 240 mm disc           Front Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	Charger	On-board charger: 6.6 kW ( Level 1 & Level 2 compatible)
Level 2 (240 V)         1 hour 30 min. (0-100%)           Charging Time:         3 hours 10 min. (20-80%)           Level 1 (120 V)         5 hours 15 min. (0-100%)           DRIVETRAIN           Transmission         Clutchless direct drive           Final Drive         Chaincase with silent chain           Function         Reverse function           CHASSIS           Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/ Travel         KYB 43 mm inverted fork / 255 mm (10 in.)           Rear Suspension/ Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan† 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan 1-piston floating caliper, 240 mm disc           Front Tire         Dunlop† D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	Connector	Type 1 J1772
Level 1 (120 V)         5 hours 15 min. (0-100%)           DRIVETRAIN           Transmission         Clutchless direct drive           Final Drive         Chaincase with silent chain           Function         Reverse function           CHASSIS           Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/ Travel         KYB 43 mm inverted fork / 255 mm (10 in.)           Rear Suspension/ Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan¹ 2-piston floating caliper, 240 mm disc           Front Tire         Dunlop¹ 6065 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)		
Transmission Clutchless direct drive  Final Drive Chaincase with silent chain  Function Reverse function  CHASSIS  Swingarm Single-sided swingarm  Rake 30°  Trail 118 mm (14.6 in.)  Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.)  Travel Rear Suspension/ Travel rebound / 255 mm (10 in.)  Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc  Rear Brake J.Juan¹ 1-piston floating caliper, 240 mm disc  Front Tire Dunlop¹ D605 90/90 R21 (with tube)  Rear Tire Dunlop D605 120/80 R18 (with tube)  Wheels Spoked wheel, Carbon black  Front Wheel Size 533 x 47 mm (21 x 1.85 in.)		
Final Drive Chaincase with silent chain Function Reverse function  CHASSIS  Swingarm Single-sided swingarm  Rake 30°  Trail 118 mm (14.6 in.)  Front Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.)  Travel  Rear Suspension/ KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)  Front Brake J.Juan¹ 2-piston floating caliper, 320 mm disc  Rear Brake J.Juan¹ 1-piston floating caliper, 240 mm disc  Front Tire Dunlop¹ D605 90/90 R21 (with tube)  Rear Tire Dunlop D605 120/80 R18 (with tube)  Wheels Spoked wheel, Carbon black  Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	DRIVETRAIN	
Function         Reverse function           CHASSIS         Swingarm         Single-sided swingarm           Rake         30°         Trail         118 mm (14.6 in.)           Front Suspension/ Travel         KYB 43 mm inverted fork / 255 mm (10 in.)           Rear Suspension/ Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan 1-piston floating caliper, 240 mm disc           Front Tire         Dunlop¹ D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	Transmission	Clutchless direct drive
CHASSIS           Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/         KYB 43 mm inverted fork / 255 mm (10 in.)           Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan¹-piston floating caliper, 240 mm disc           Front Tire         Dunlop¹ D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	Final Drive	Chaincase with silent chain
Swingarm         Single-sided swingarm           Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/ Travel         KYB 43 mm inverted fork / 255 mm (10 in.)           Rear Suspension/ Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan 1-piston floating caliper, 240 mm disc           Front Tire         Dunlop¹ D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	Function	Reverse function
Rake         30°           Trail         118 mm (14.6 in.)           Front Suspension/ Travel         KYB 43 mm inverted fork / 255 mm (10 in.)           Rear Suspension/ Travel         KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)           Front Brake         J.Juan¹ 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan 1-piston floating caliper, 240 mm disc           Front Tire         Dunlop¹ D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)	CHASSIS	
Trail 118 mm (14.6 in.)  Front Suspension/ Travel  Rear Suspension/ KYB 43 mm inverted fork / 255 mm (10 in.)  Travel  Rear Suspension/ Travel rebound / 255 mm (10 in.)  Front Brake J.Juan† 2-piston floating caliper, 320 mm disc  Rear Brake J.Juan 1-piston floating caliper, 240 mm disc  Front Tire Dunlop† D605 90/90 R21 (with tube)  Rear Tire Dunlop D605 120/80 R18 (with tube)  Wheels Spoked wheel, Carbon black  Front Wheel Size 533 x 47 mm (21 x 1.85 in.)	Swingarm	Single-sided swingarm
Front Suspension/ Travel  Rear Suspension/ Travel  Rear Suspension/ Travel  KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)  Front Brake  J.Juan¹ 2-piston floating caliper, 320 mm disc  Rear Brake  J.Juan¹ 1-piston floating caliper, 240 mm disc  Front Tire  Dunlop¹ D605 90/90 R21 (with tube)  Rear Tire  Dunlop D605 120/80 R18 (with tube)  Wheels  Spoked wheel, Carbon black  Front Wheel Size  533 x 47 mm (21 x 1.85 in.)	Rake	30°
Travel  Rear Suspension/ Travel  KYB HPG shock with adjustable preload, compression and rebound / 255 mm (10 in.)  Front Brake  J.Juan¹ 2-piston floating caliper, 320 mm disc  Rear Brake  J.Juan¹-piston floating caliper, 240 mm disc  Front Tire  Dunlop¹ D605 90/90 R21 (with tube)  Rear Tire  Dunlop D605 120/80 R18 (with tube)  Wheels  Spoked wheel, Carbon black  Front Wheel Size  533 x 47 mm (21 x 1.85 in.)	Trail	118 mm (14.6 in.)
Travel         rebound / 255 mm (10 in.)           Front Brake         J.Juan† 2-piston floating caliper, 320 mm disc           Rear Brake         J.Juan 1-piston floating caliper, 240 mm disc           Front Tire         Dunlop† D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm (21 x 1.85 in.)		KYB 43 mm inverted fork / 255 mm (10 in.)
Rear Brake         J.Juan 1-piston floating caliper, 240 mm disc           Front Tire         Dunlop† D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm ( 21 x 1.85 in.)		
Front Tire         Dunlop¹ D605 90/90 R21 (with tube)           Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm ( 21 x 1.85 in.)	Front Brake	J.Juan <sup>†</sup> 2-piston floating caliper, 320 mm disc
Rear Tire         Dunlop D605 120/80 R18 (with tube)           Wheels         Spoked wheel, Carbon black           Front Wheel Size         533 x 47 mm ( 21 x 1.85 in.)	Rear Brake	J.Juan 1-piston floating caliper, 240 mm disc
Wheels Spoked wheel, Carbon black Front Wheel Size 533 x 47 mm ( 21 x 1.85 in.)	Front Tire	Dunlop <sup>†</sup> D605 90/90 R21 (with tube)
Front Wheel Size 533 x 47 mm ( 21 x 1.85 in.)	Rear Tire	Dunlop D605 120/80 R18 (with tube)
	Wheels	Spoked wheel, Carbon black
Rear Wheel Size 457 x 63.5 mm (18 x 2.5 in.)	Front Wheel Size	533 x 47 mm ( 21 x 1.85 in.)
	Rear Wheel Size	457 x 63.5 mm (18 x 2.5 in.)

### COLOR

Sterling Silver S	atin
DIMENSIONS	
L x W x H (with mirrors)	2,204 x 861 x 1,414 mm(86.8 x 33.9 x 55.7 in.)
Wheelbase	1,503 mm (59 in.)
Seat Height	865 mm (34 in.)
Ground Clearance	274 mm (10.8 in.)
Curb Weight	187 kg (412 lb)
Maximum Vehicle Load	338 kg (745 lb)
INSTRUMENTATION	
Туре	10,25 in, touchscreen display with BRP Connect
Navigation System	Apple CarPlay
Drive Modes	Normal, ECO, Rain, Sport, Off-Road, Off-Road+
Handlebar Control	Backlit handlebar control module
SAFETY & SECURITY	•
ABS	Anti-Lock Braking System
MTC	Motorcycle Traction Control
WARRANTY & EXTER	NDED SERVICE
Vehicle Warranty	2 years
Battery Warranty	5 years / 31,068 miles (50,000 km)
Extended Service Terms	
FEATURES	
	LED headlight Glove box with USB port LinQ anchor points Skid plate LinQ Windshield Signature LED lights Vehicle cover Exclusive '73 package color and trims