



RS 457 GP Replica - TECHNICAL SPECIFICATION

TYPE	2 parallel forward facing cylinders, 4 valves per cylinder, liquid-cooled with Ride-By-Wire
DISPLACEMENT	457 cc
BORE AND STROKE	69 x 61,1 mm
MAX. POWER	47,6 CV (35 kW) a 9.400 giri/min
MAX. TORQUE	43,5 Nm a 6.700 giri/min
CLUTCH	Multiplate wet clutch with slipper system
GEARBOX	6 gears
FRAME	Dual beam aluminium frame
FRONT SUSPENSION	41mm upside-down fork, adjustable preload, 120mm travel
REAR SUSPENSION	Monoshock, adjustable preload, 130 mm wheel travel
FRONT BRAKE	320 mm floating disc. ByBre 4-piston radial calliper
REAR BRAKE	220 mm disc. ByBre single piston calliper
FRONT WHEEL	17" x 3" Aluminium alloy rim
REAR WHEEL	17" x 4.5" Aluminium alloy rim
SEAT HEIGHT	800 mm
FUEL TANK CAPACITY	13 litres
WET WEIGHT*	175 Kg
STANDARD FEATURES	LED headlight assembly. Engine maps (AEM), dual-channel ABS with anti roll-over system (2 maps), traction control (ATC), 3 riding modes. 5" TFT instrument panel. Metal braided brake hoses. Backlit handlebar controls. Passenger Seat Cover. Quickshift. Racing Brake Pads (Street Legal).

*In compliance with the VO (EU) 168/2013 standards, with all operating fluids, with standard equipment and fuel tank filled to 90% capacity