## **MY26 COMMANDER MAX XT 1000R**



ENGINES	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD auto-locking QE front differential
Driving Assistance	CVT Engine Braking SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar / 15 in. (38.1 cm) suspension travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 15 in. (38.1 cm) suspension travel
Rear Shocks	Twin tube gas charged shocks
TIRES / WHEELS	
Front / Rear Tires	XPS Trail King 28 x 9/11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front & Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

Profiled cage ROPS approved  160.4 x 64 x 76.2 in. (407.4 x 162.6 x 193.5 cm)  120.6 in. (306.3 cm)  13 in. (33 cm)  29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)  600 lb (272.2 kg)  2,000 lb (907.2 kg)  1,280 lb (580.6 kg)  Total: 8.5 gal (32.1 L)  10 gal (38 L)  7.6 in. wide digital display with keypad  DC outlet (10-A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
120.6 in. (306.3 cm)  13 in. (33 cm)  29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)  600 lb (272.2 kg)  2,000 lb (907.2 kg)  1,280 lb (580.6 kg)  Total: 8.5 gal (32.1 L)  10 gal (38 L)  7.6 in. wide digital display with keypad  DC outlet (10-A)  RF Digitally Encoded Security System (D.E.S.S.™)
13 in. (33 cm) 29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm) 600 lb (272.2 kg) 2,000 lb (907.2 kg) 1,280 lb (580.6 kg) Total: 8.5 gal (32.1 L) 10 gal (38 L)  7.6 in. wide digital display with keypad DC outlet (10-A) RF Digitally Encoded Security System (D.E.S.S.™)
29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm) 600 lb (272.2 kg) 2,000 lb (907.2 kg) 1,280 lb (580.6 kg) Total: 8.5 gal (32.1 L) 10 gal (38 L)  7.6 in. wide digital display with keypad DC outlet (10-A) RF Digitally Encoded Security System (D.E.S.S.™)
600 lb (272.2 kg) 2,000 lb (907.2 kg) 1,280 lb (580.6 kg) Total: 8.5 gal (32.1 L) 10 gal (38 L)  7.6 in. wide digital display with keypad DC outlet (10-A) RF Digitally Encoded Security System (D.E.S.S.™)
2,000 lb (907.2 kg)  1,280 lb (580.6 kg)  Total: 8.5 gal (32.1 L)  10 gal (38 L)  7.6 in. wide digital display with keypad  DC outlet (10-A)  RF Digitally Encoded Security System (D.E.S.S.™)
1,280 lb (580.6 kg)  Total: 8.5 gal (32.1 L)  10 gal (38 L)  7.6 in. wide digital display with keypad  DC outlet (10-A)  RF Digitally Encoded Security System (D.E.S.S.™)
Total: 8.5 gal (32.1 L)  10 gal (38 L)  7.6 in. wide digital display with keypad  DC outlet (10-A)  RF Digitally Encoded Security System (D.E.S.S.™)
10 gal (38 L)  7.6 in. wide digital display with keypad  DC outlet (10-A)  RF Digitally Encoded Security System (D.E.S.S.™)
7.6 in. wide digital display with keypad DC outlet (10-A) RF Digitally Encoded Security System (D.E.S.S.™)
DC outlet (10-A) RF Digitally Encoded Security System (D.E.S.S.™)
DC outlet (10-A) RF Digitally Encoded Security System (D.E.S.S.™)
RF Digitally Encoded Security System (D.E.S.S.™)
mar darry drop battori
650-W
Front lighting output 110-W LED Signature LED tail lights
4,500 lb (2,041 kg) winch with synthetic cable
Adjustable tilt steering
Premium half doors Full heavy-duty HMW plastic skid plate Mudguards XT Front bumper Full roof
2 in. hitch receiver





1-year BRP limited warranty



Factory warranty