

2026 MAVERICK X3 X_{DS}



Triple Black
Dusty Navy

PACKAGE OPTIONS

- 10.25 in. touchscreen display, telescopic steering wheel, front & back cameras
- Smart-Shox™** Technology featuring DDA Valve, 10.25 in. touchscreen display, telescopic steering wheel, front & back cameras

PACKAGE HIGHLIGHTS

- Smart-Lok™** front differential
- FOX® 2.5 PODIUM RC2¹
- Belt monitoring system
- 850 W magneto
- 30 in. XPS Trac Force tires
- 14 in. aluminum beadlock wheels
- 4-point harness with shoulder pads
- Full hard roof
- Full heavy-duty HMW plastic skid plate
- 7.6 in. digital display with keypad
- X-package graphics/seats
- Can-Am LED signature

ENGINE		TURBO RR
Type		200 hp, Rotax® ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System		Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission		pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train		Lockable front differential with exclusive Smart-Lok True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering		High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS		
Front Suspension		Arched double A-arm with sway bar / 20 in. (50.8 cm) suspension travel
Front Shocks		FOX 2.5 PODIUM RC2 Piggyback with dual-speed compression and rebound adjustments OR FOX 2.5 PODIUM ¹ Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension		4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) suspension travel
Rear Shocks		FOX 2.5 PODIUM RC2 Piggyback with dual-speed compression, rebound adjustments and bottom-out control OR FOX 3.0 PODIUM ¹ Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
TIRES & WHEELS		
Front / Rear Tires		XPS Trac Force 30 x 10 x 14 in.
Wheels		14 in. cast-aluminum beadlock
BRAKES		
Front		Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear		Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,579 lb (715.9 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	132 x 64 x 65.7 in. (335.3 x 162.5 x 166.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ® quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. digital display with keypad OR 4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Instrumentation	DC outlet (10 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlight LED signature LED taillights
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper Quarter-doors Full hard roof 4-point harness with shoulder pads Full heavy-duty HMW plastic skid plate Rear tow hook

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry. **Smart-Shox was developed in conjunction with FOX and Tractive Industries, a market leader in the suspension industry.

