

SPECIFICATII TEHNICE

MOTOR

Tip	eSP+ SOHC - 4 timpi, 4 supape
Capacitate cilindrica	125 cc
Diametru x Cursa	53.5 x 55.5 mm
Raport compresie	11.5 : 1
Putere maxima	12.5 CP / 8.750 rot/min
Cuplu maxim	11.7 Nm / 6.500 rot/min

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Consum carburant	2.1 l/100 km
Capacitate rezervor carburant	8.1 l
Capacitate rezervor ulei	0.9 l

EMISII CO2 & NORMA DE POLUARE

Norma de poluare	Euro 5+
Emisii CO2	49 g/km

SISTEM ELECTRIC

Sistem de aprindere	Gestionat electronic
Demaror	Electric
Lumini	LED

TRANSMISIE

Tip	CVT
Ambreiaj	Automatic; centrifugal
Transmisie finala	V-Matic

Honda Intelligent Security System

Smart Key	
Ecran LCD	
Priza USB-C	
Lumini Full LED	
Honda Selectable Torque Control (HSTC)	

CULORI DISPONIBILE

MAT GALAXY BLACK METALLIC



PEARL SNOWFLAKE WHITE



PEARL DARK ASH BLUE



MAT DIM GRAY METALLIC



Tip	Fata	Furca telescopica (31 mm), cursa 89 mm
	Spate	Brat articulata din aluminiu cu suspensie dubla, cursa 95 mm
Jante	Fata	14M/C x MT2.75
	Spate	13M/C x MT3.50
Anvelope	Fata	110/70-14M/C 50P
	Spate	130/70-13M/C 63P

Fata	Disc hidraulic de 220 mm, etrier cu 2 pistoane, ABS
Spate	Disc hidraulic de 220 mm, etrier cu 1 piston

CADRU

Tip	Duplex Tubular - Otel
Dimensiuni (L x l x i)	1.935 x 740 x 1.125 mm
Ampatament	1.315 mm
Unghi inclinare furca	26.5°
Cursa	80 mm
Inaltime sa	763 mm
Garda la sol	135 mm
Masa proprie	133 kg