

2027 MAVERICK R X RS 999T DCT



■ Triple Black

PACKAGE HIGHLIGHTS

- 77 in. 4 Link Trailing arm with aluminum HD tall knuckle
- Smart-Lok™ front differential
- FOX† 3.0 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments
- 10.25 in. touchscreen display
- 32 in. XPS Trac Force tires
- 16 in. aluminum flow formed beadlock wheels
- Front and rear cameras
- Telescopic steering wheel with infotainment controls
- Full hard roof / Full plastic skid plate
- 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature
- Center dashboard storage with cell phone holder
- X-package graphics/seats
- 1700-W Magneto / Horn with carling

ENGINES

	999T
Type	240 hp (176.5 kW), Rotax 999 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Rotax DCT, 7 Speed with High & Low range
Drive Train	Lockable front differential with exclusive Smart-Lok True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	High torque Gen 2 Tri-Mode DPS

SUSPENSIONS

Front Suspension	Forged Aluminum heavy duty Tall Knuckle - Double A-arm with sway bar / 25 in. (63.5 cm) suspension travel
Front Shocks	FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4 Link Trailing arm with Forged Aluminum heavy duty Tall Knuckle / 25.5 in. (64.8 cm) suspension travel
Rear Shocks	FOX† 3.0 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments

TIRES / WHEELS

Front / Rear Tires	XPS Trac Force 32 x 10 x 16 in.
Wheels	16 in. Aluminum flow formed beadlock

BRAKES

Front	32 mm hydraulic triple piston caliper with a 265 mm disc
Rear	30 mm hydraulic twin piston caliper with a 255 mm disc

DIMENSIONS / CAPACITIES

Cage	High strength (Dual phase) steel tubing and stampings
Estimated Dry Weight*	1,083 kg
L x W x H	142 x 78.1 x 71.5 in. (360.7 x 198.5 x 181.5 cm)
Wheelbase	110 in. (279.1 cm)
Ground Clearance	17 in. (43.2 cm)
Cargo Box Capacity	90 kg
Storage Capacity	Total: 8.1 L
Fuel Capacity	50 L

FEATURES

Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Magneto	1700-W
Instrumentation	USB A (2 charging port & 1 communication port) DC outlet (10-A)
Lighting	Premium high-performance LED headlights Can-Am LED signature
Winch	Winch-ready bumper (2,041 kg winch not installed)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Protection	Full hard roof Premium half doors Front lower deflector Front / Rear anchor Full plastic skid plate

WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

REQUEST A QUOTE



©2026 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

