

2027

KLX[®]230SM ABS



POWER

Engine	4-stroke single, SOHC,air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Horsepower	17hp ¹ @ 8,000 rpm
Maximum Torque	13.3lb-ft @ 6,400 rpm
Fuel System	DFI [®] with 32mm throttle body
Ignition	TCBIwith Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / WheelTravel	37mmtelescopic fork/7.4 in
Rear Suspension / Wheel Travel	New Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	110/70-17

Rear Tire	120/70-17
Front Brakes	Single 300mm semi-floating petal disc with a dual-piston caliper and ABS
Rear Brakes	Single 220mm petal disc with single-piston caliper and ABS

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.9°/3.0 in
Overall Length	80.1 in
Overall Width	33.3 in
Overall Height	44.3 in
Ground Clearance	8.7 in
Seat Height	33.1 in
Estimated Dry Weight	286.5lb** 50-State Model; 284.4lb** 49-State Model
Curb Weight	302.1lb* 50-State Model; 299.9lb* 49-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT [®] ,LCDInstrumentation with Smartphone Connectivity via RIDEOLOGYTHEAPP MOTORCYCLE
Color Choices	Neon Green/Ebony